

Linux generic IRQ handling

Thomas Gleixner <tglx@linutronix.de>
Ingo Molnar <mingo@elte.hu>

Linux generic IRQ handling

by Thomas Gleixner and Ingo Molnar

Copyright © 2005-2010 Thomas Gleixner

Copyright © 2005-2006 Ingo Molnar

This documentation is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License version 2 as published by the Free Software Foundation.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

For more details see the file COPYING in the source distribution of Linux.

Table of Contents

| | |
|--|----|
| 1. Introduction | 1 |
| 2. Rationale | 2 |
| 3. Known Bugs And Assumptions | 3 |
| 4. Abstraction layers | 4 |
| Interrupt control flow | 4 |
| High-level Driver API | 4 |
| High-level IRQ flow handlers | 4 |
| Default flow implementations | 5 |
| Default flow handler implementations | 6 |
| Quirks and optimizations | 7 |
| Delayed interrupt disable | 7 |
| Chip-level hardware encapsulation | 7 |
| 5. __do_IRQ entry point | 9 |
| 6. Locking on SMP | 10 |
| 7. Generic interrupt chip | 11 |
| irq_gc_mask_set_bit | 12 |
| irq_gc_mask_clr_bit | 13 |
| irq_gc_ack_set_bit | 14 |
| irq_alloc_generic_chip | 15 |
| irq_alloc_domain_generic_chips | 16 |
| irq_get_domain_generic_chip | 17 |
| irq_setup_generic_chip | 18 |
| irq_setup_alt_chip | 19 |
| irq_remove_generic_chip | 20 |
| 8. Structures | 21 |
| struct irq_data | 22 |
| struct irq_chip | 23 |
| struct irq_chip_regs | 25 |
| struct irq_chip_type | 26 |
| struct irq_chip_generic | 27 |
| enum irq_gc_flags | 29 |
| struct irqaction | 30 |
| struct irq_affinity_notify | 31 |
| irq_set_affinity | 32 |
| irq_force_affinity | 33 |
| 9. Public Functions Provided | 34 |
| synchronize_hardirq | 35 |
| synchronize_irq | 36 |
| irq_set_affinity_notifier | 37 |
| disable_irq_nosync | 38 |
| disable_irq | 39 |
| enable_irq | 40 |
| irq_set_irq_wake | 41 |
| irq_wake_thread | 42 |
| setup_irq | 43 |
| remove_irq | 44 |
| free_irq | 45 |
| request_threaded_irq | 46 |
| request_any_context_irq | 47 |
| irq_set_chip | 48 |
| irq_set_irq_type | 49 |

| | |
|---------------------------------------|----|
| irq_set_handler_data | 50 |
| irq_set_chip_data | 51 |
| handle_simple_irq | 52 |
| handle_level_irq | 53 |
| handle_fasteoi_irq | 54 |
| handle_edge_irq | 55 |
| 10. Internal Functions Provided | 56 |
| irq_get_next_irq | 57 |
| handle_bad_irq | 58 |
| irq_set_msi_desc_off | 59 |
| irq_set_msi_desc | 60 |
| irq_disable | 61 |
| handle_edge_eoi_irq | 62 |
| handle_percpu_irq | 63 |
| handle_percpu_devid_irq | 64 |
| irq_cpu_online | 65 |
| irq_cpu_offline | 66 |
| 11. Credits | 67 |

Chapter 1. Introduction

The generic interrupt handling layer is designed to provide a complete abstraction of interrupt handling for device drivers. It is able to handle all the different types of interrupt controller hardware. Device drivers use generic API functions to request, enable, disable and free interrupts. The drivers do not have to know anything about interrupt hardware details, so they can be used on different platforms without code changes.

This documentation is provided to developers who want to implement an interrupt subsystem based for their architecture, with the help of the generic IRQ handling layer.

Chapter 2. Rationale

The original implementation of interrupt handling in Linux uses the `__do_IRQ()` super-handler, which is able to deal with every type of interrupt logic.

Originally, Russell King identified different types of handlers to build a quite universal set for the ARM interrupt handler implementation in Linux 2.5/2.6. He distinguished between:

- Level type
- Edge type
- Simple type

During the implementation we identified another type:

- Fast EOI type

In the SMP world of the `__do_IRQ()` super-handler another type was identified:

- Per CPU type

This split implementation of high-level IRQ handlers allows us to optimize the flow of the interrupt handling for each specific interrupt type. This reduces complexity in that particular code path and allows the optimized handling of a given type.

The original general IRQ implementation used `hw_interrupt_type` structures and their `->ack()`, `->end()` [etc.] callbacks to differentiate the flow control in the super-handler. This leads to a mix of flow logic and low-level hardware logic, and it also leads to unnecessary code duplication: for example in i386, there is an `ioapic_level_irq` and an `ioapic_edge_irq` IRQ-type which share many of the low-level details but have different flow handling.

A more natural abstraction is the clean separation of the 'irq flow' and the 'chip details'.

Analysing a couple of architecture's IRQ subsystem implementations reveals that most of them can use a generic set of 'irq flow' methods and only need to add the chip-level specific code. The separation is also valuable for (sub)architectures which need specific quirks in the IRQ flow itself but not in the chip details - and thus provides a more transparent IRQ subsystem design.

Each interrupt descriptor is assigned its own high-level flow handler, which is normally one of the generic implementations. (This high-level flow handler implementation also makes it simple to provide demultiplexing handlers which can be found in embedded platforms on various architectures.)

The separation makes the generic interrupt handling layer more flexible and extensible. For example, an (sub)architecture can use a generic IRQ-flow implementation for 'level type' interrupts and add a (sub)architecture specific 'edge type' implementation.

To make the transition to the new model easier and prevent the breakage of existing implementations, the `__do_IRQ()` super-handler is still available. This leads to a kind of duality for the time being. Over time the new model should be used in more and more architectures, as it enables smaller and cleaner IRQ subsystems. It's deprecated for three years now and about to be removed.

Chapter 3. Known Bugs And Assumptions

None (knock on wood).

Chapter 4. Abstraction layers

There are three main levels of abstraction in the interrupt code:

1. High-level driver API
2. High-level IRQ flow handlers
3. Chip-level hardware encapsulation

Interrupt control flow

Each interrupt is described by an interrupt descriptor structure `irq_desc`. The interrupt is referenced by an 'unsigned int' numeric value which selects the corresponding interrupt description structure in the descriptor structures array. The descriptor structure contains status information and pointers to the interrupt flow method and the interrupt chip structure which are assigned to this interrupt.

Whenever an interrupt triggers, the low-level architecture code calls into the generic interrupt code by calling `desc->handle_irq()`. This high-level IRQ handling function only uses `desc->irq_data.chip` primitives referenced by the assigned chip descriptor structure.

High-level Driver API

The high-level Driver API consists of following functions:

- `request_irq()`
- `free_irq()`
- `disable_irq()`
- `enable_irq()`
- `disable_irq_nosync()` (SMP only)
- `synchronize_irq()` (SMP only)
- `irq_set_irq_type()`
- `irq_set_irq_wake()`
- `irq_set_handler_data()`
- `irq_set_chip()`
- `irq_set_chip_data()`

See the autogenerated function documentation for details.

High-level IRQ flow handlers

The generic layer provides a set of pre-defined irq-flow methods:

- `handle_level_irq`

- `handle_edge_irq`
- `handle_fasteoi_irq`
- `handle_simple_irq`
- `handle_percpu_irq`
- `handle_edge_eoi_irq`
- `handle_bad_irq`

The interrupt flow handlers (either pre-defined or architecture specific) are assigned to specific interrupts by the architecture either during bootup or during device initialization.

Default flow implementations

Helper functions

The helper functions call the chip primitives and are used by the default flow implementations. The following helper functions are implemented (simplified excerpt):

```
default_enable(struct irq_data *data)
{
    desc->irq_data.chip->irq_unmask(data);
}

default_disable(struct irq_data *data)
{
    if (!delay_disable(data))
        desc->irq_data.chip->irq_mask(data);
}

default_ack(struct irq_data *data)
{
    chip->irq_ack(data);
}

default_mask_ack(struct irq_data *data)
{
    if (chip->irq_mask_ack) {
        chip->irq_mask_ack(data);
    } else {
        chip->irq_mask(data);
        chip->irq_ack(data);
    }
}

noop(struct irq_data *data)
{
}
```

Default flow handler implementations

Default Level IRQ flow handler

`handle_level_irq` provides a generic implementation for level-triggered interrupts.

The following control flow is implemented (simplified excerpt):

```
desc->irq_data.chip->irq_mask_ack();
handle_irq_event(desc->action);
desc->irq_data.chip->irq_unmask();
```

Default Fast EOI IRQ flow handler

`handle_fasteoi_irq` provides a generic implementation for interrupts, which only need an EOI at the end of the handler.

The following control flow is implemented (simplified excerpt):

```
handle_irq_event(desc->action);
desc->irq_data.chip->irq_eoi();
```

Default Edge IRQ flow handler

`handle_edge_irq` provides a generic implementation for edge-triggered interrupts.

The following control flow is implemented (simplified excerpt):

```
if (desc->status & running) {
    desc->irq_data.chip->irq_mask_ack();
    desc->status |= pending | masked;
    return;
}
desc->irq_data.chip->irq_ack();
desc->status |= running;
do {
    if (desc->status & masked)
        desc->irq_data.chip->irq_unmask();
    desc->status &= ~pending;
    handle_irq_event(desc->action);
} while (status & pending);
desc->status &= ~running;
```

Default simple IRQ flow handler

`handle_simple_irq` provides a generic implementation for simple interrupts.

Note: The simple flow handler does not call any handler/chip primitives.

The following control flow is implemented (simplified excerpt):

```
handle_irq_event(desc->action);
```

Default per CPU flow handler

`handle_percpu_irq` provides a generic implementation for per CPU interrupts.

Per CPU interrupts are only available on SMP and the handler provides a simplified version without locking.

The following control flow is implemented (simplified excerpt):

```
if (desc->irq_data.chip->irq_ack)
    desc->irq_data.chip->irq_ack();
handle_irq_event(desc->action);
if (desc->irq_data.chip->irq_eoi)
    desc->irq_data.chip->irq_eoi();
```

EOI Edge IRQ flow handler

`handle_edge_eoi_irq` provides an abomination of the edge handler which is solely used to tame a badly wreckaged irq controller on powerpc/cell.

Bad IRQ flow handler

`handle_bad_irq` is used for spurious interrupts which have no real handler assigned..

Quirks and optimizations

The generic functions are intended for 'clean' architectures and chips, which have no platform-specific IRQ handling quirks. If an architecture needs to implement quirks on the 'flow' level then it can do so by overriding the high-level irq-flow handler.

Delayed interrupt disable

This per interrupt selectable feature, which was introduced by Russell King in the ARM interrupt implementation, does not mask an interrupt at the hardware level when `disable_irq()` is called. The interrupt is kept enabled and is masked in the flow handler when an interrupt event happens. This prevents losing edge interrupts on hardware which does not store an edge interrupt event while the interrupt is disabled at the hardware level. When an interrupt arrives while the `IRQ_DISABLED` flag is set, then the interrupt is masked at the hardware level and the `IRQ_PENDING` bit is set. When the interrupt is re-enabled by `enable_irq()` the pending bit is checked and if it is set, the interrupt is resent either via hardware or by a software resend mechanism. (It's necessary to enable `CONFIG_HARDIRQS_SW_RESEND` when you want to use the delayed interrupt disable feature and your hardware is not capable of retriggering an interrupt.) The delayed interrupt disable is not configurable.

Chip-level hardware encapsulation

The chip-level hardware descriptor structure `irq_chip` contains all the direct chip relevant functions, which can be utilized by the irq flow implementations.

- `irq_ack()`
- `irq_mask_ack()` - Optional, recommended for performance
- `irq_mask()`
- `irq_unmask()`
- `irq_eoi()` - Optional, required for EOI flow handlers
- `irq_retrigger()` - Optional
- `irq_set_type()` - Optional
- `irq_set_wake()` - Optional

These primitives are strictly intended to mean what they say: ack means ACK, masking means masking of an IRQ line, etc. It is up to the flow handler(s) to use these basic units of low-level functionality.

Chapter 5. `__do_IRQ` entry point

The original implementation `__do_IRQ()` was an alternative entry point for all types of interrupts. It no longer exists.

This handler turned out to be not suitable for all interrupt hardware and was therefore reimplemented with split functionality for edge/level/simple/percpu interrupts. This is not only a functional optimization. It also shortens code paths for interrupts.

Chapter 6. Locking on SMP

The locking of chip registers is up to the architecture that defines the chip primitives. The per-irq structure is protected via desc->lock, by the generic layer.

Chapter 7. Generic interrupt chip

To avoid copies of identical implementations of IRQ chips the core provides a configurable generic interrupt chip implementation. Developers should check carefully whether the generic chip fits their needs before implementing the same functionality slightly differently themselves.

Name

`irq_gc_mask_set_bit` — Mask chip via setting bit in mask register

Synopsis

```
void irq_gc_mask_set_bit (struct irq_data * d);
```

Arguments

d `irq_data`

Description

Chip has a single mask register. Values of this register are cached and protected by `gc->lock`

Name

`irq_gc_mask_clr_bit` — Mask chip via clearing bit in mask register

Synopsis

```
void irq_gc_mask_clr_bit (struct irq_data * d);
```

Arguments

d `irq_data`

Description

Chip has a single mask register. Values of this register are cached and protected by `gc->lock`

Name

`irq_gc_ack_set_bit` — Ack pending interrupt via setting bit

Synopsis

```
void irq_gc_ack_set_bit (struct irq_data * d);
```

Arguments

d `irq_data`

Name

`irq_alloc_generic_chip` — Allocate a generic chip and initialize it

Synopsis

```
struct irq_chip_generic * irq_alloc_generic_chip (const char *  
name, int num_ct, unsigned int irq_base, void __iomem * reg_base,  
irq_flow_handler_t handler);
```

Arguments

| | |
|-----------------|--|
| <i>name</i> | Name of the irq chip |
| <i>num_ct</i> | Number of irq_chip_type instances associated with this |
| <i>irq_base</i> | Interrupt base nr for this chip |
| <i>reg_base</i> | Register base address (virtual) |
| <i>handler</i> | Default flow handler associated with this chip |

Description

Returns an initialized `irq_chip_generic` structure. The chip defaults to the primary (index 0) `irq_chip_type` and *handler*

Name

`irq_alloc_domain_generic_chips` — Allocate generic chips for an irq domain

Synopsis

```
int irq_alloc_domain_generic_chips (struct irq_domain * d, int
irqs_per_chip, int num_ct, const char * name, irq_flow_handler_t
handler, unsigned int clr, unsigned int set, enum irq_gc_flags gcflags);
```

Arguments

| | |
|----------------------|---|
| <i>d</i> | irq domain for which to allocate chips |
| <i>irqs_per_chip</i> | Number of interrupts each chip handles |
| <i>num_ct</i> | Number of <code>irq_chip_type</code> instances associated with this |
| <i>name</i> | Name of the irq chip |
| <i>handler</i> | Default flow handler associated with these chips |
| <i>clr</i> | IRQ_* bits to clear in the mapping function |
| <i>set</i> | IRQ_* bits to set in the mapping function |
| <i>gcflags</i> | Generic chip specific setup flags |

Name

`irq_get_domain_generic_chip` — Get a pointer to the generic chip of a `hw_irq`

Synopsis

```
struct  irq_chip_generic  *  irq_get_domain_generic_chip  (struct  
irq_domain * d, unsigned int hw_irq);
```

Arguments

d irq domain pointer

hw_irq Hardware interrupt number

Name

`irq_setup_generic_chip` — Setup a range of interrupts with a generic chip

Synopsis

```
void irq_setup_generic_chip (struct irq_chip_generic * gc, u32 msk, enum  
irq_gc_flags flags, unsigned int clr, unsigned int set);
```

Arguments

| | |
|--------------|---|
| <i>gc</i> | Generic irq chip holding all data |
| <i>msk</i> | Bitmask holding the irqs to initialize relative to <code>gc->irq_base</code> |
| <i>flags</i> | Flags for initialization |
| <i>clr</i> | IRQ_* bits to clear |
| <i>set</i> | IRQ_* bits to set |

Description

Set up max. 32 interrupts starting from `gc->irq_base`. Note, this initializes all interrupts to the primary `irq_chip_type` and its associated handler.

Name

`irq_setup_alt_chip` — Switch to alternative chip

Synopsis

```
int irq_setup_alt_chip (struct irq_data * d, unsigned int type);
```

Arguments

d `irq_data` for this interrupt

type Flow type to be initialized

Description

Only to be called from `chip->irq_set_type` callbacks.

Name

`irq_remove_generic_chip` — Remove a chip

Synopsis

```
void irq_remove_generic_chip (struct irq_chip_generic * gc, u32 msk,  
unsigned int clr, unsigned int set);
```

Arguments

gc Generic irq chip holding all data

msk Bitmask holding the irqs to initialize relative to `gc->irq_base`

clr IRQ_* bits to clear

set IRQ_* bits to set

Description

Remove up to 32 interrupts starting from `gc->irq_base`.

Chapter 8. Structures

This chapter contains the autogenerated documentation of the structures which are used in the generic IRQ layer.

Name

struct irq_data — per irq and irq chip data passed down to chip functions

Synopsis

```
struct irq_data {
    u32 mask;
    unsigned int irq;
    unsigned long hwirq;
    unsigned int node;
    unsigned int state_use_accessors;
    struct irq_chip * chip;
    struct irq_domain * domain;
    void * handler_data;
    void * chip_data;
    struct msi_desc * msi_desc;
    cpumask_var_t affinity;
};
```

Members

| | |
|---------------------|--|
| mask | precomputed bitmask for accessing the chip registers |
| irq | interrupt number |
| hwirq | hardware interrupt number, local to the interrupt domain |
| node | node index useful for balancing |
| state_use_accessors | status information for irq chip functions. Use accessor functions to deal with it |
| chip | low level interrupt hardware access |
| domain | Interrupt translation domain; responsible for mapping between hwirq number and linux irq number. |
| handler_data | per-IRQ data for the irq_chip methods |
| chip_data | platform-specific per-chip private data for the chip methods, to allow shared chip implementations |
| msi_desc | MSI descriptor |
| affinity | IRQ affinity on SMP |

Description

The fields here need to overlay the ones in irq_desc until we cleaned up the direct references and switched everything over to irq_data.

Name

struct irq_chip — hardware interrupt chip descriptor

Synopsis

```
struct irq_chip {
    const char * name;
    unsigned int (* irq_startup) (struct irq_data *data);
    void (* irq_shutdown) (struct irq_data *data);
    void (* irq_enable) (struct irq_data *data);
    void (* irq_disable) (struct irq_data *data);
    void (* irq_ack) (struct irq_data *data);
    void (* irq_mask) (struct irq_data *data);
    void (* irq_mask_ack) (struct irq_data *data);
    void (* irq_unmask) (struct irq_data *data);
    void (* irq_eoi) (struct irq_data *data);
    int (* irq_set_affinity) (struct irq_data *data, const struct cpumask *dest, bool);
    int (* irq_retrigger) (struct irq_data *data);
    int (* irq_set_type) (struct irq_data *data, unsigned int flow_type);
    int (* irq_set_wake) (struct irq_data *data, unsigned int on);
    void (* irq_bus_lock) (struct irq_data *data);
    void (* irq_bus_sync_unlock) (struct irq_data *data);
    void (* irq_cpu_online) (struct irq_data *data);
    void (* irq_cpu_offline) (struct irq_data *data);
    void (* irq_suspend) (struct irq_data *data);
    void (* irq_resume) (struct irq_data *data);
    void (* irq_pm_shutdown) (struct irq_data *data);
    void (* irq_calc_mask) (struct irq_data *data);
    void (* irq_print_chip) (struct irq_data *data, struct seq_file *p);
    int (* irq_request_resources) (struct irq_data *data);
    void (* irq_release_resources) (struct irq_data *data);
    unsigned long flags;
};
```

Members

| | |
|--------------|---|
| name | name for /proc/interrupts |
| irq_startup | start up the interrupt (defaults to ->enable if NULL) |
| irq_shutdown | shut down the interrupt (defaults to ->disable if NULL) |
| irq_enable | enable the interrupt (defaults to chip->unmask if NULL) |
| irq_disable | disable the interrupt |
| irq_ack | start of a new interrupt |
| irq_mask | mask an interrupt source |
| irq_mask_ack | ack and mask an interrupt source |
| irq_unmask | unmask an interrupt source |

| | |
|------------------------------------|---|
| <code>irq_eoi</code> | end of interrupt |
| <code>irq_set_affinity</code> | set the CPU affinity on SMP machines |
| <code>irq_retrigger</code> | resend an IRQ to the CPU |
| <code>irq_set_type</code> | set the flow type (<code>IRQ_TYPE_LEVEL/etc.</code>) of an IRQ |
| <code>irq_set_wake</code> | enable/disable power-management wake-on of an IRQ |
| <code>irq_bus_lock</code> | function to lock access to slow bus (i2c) chips |
| <code>irq_bus_sync_unlock</code> | function to sync and unlock slow bus (i2c) chips |
| <code>irq_cpu_online</code> | configure an interrupt source for a secondary CPU |
| <code>irq_cpu_offline</code> | un-configure an interrupt source for a secondary CPU |
| <code>irq_suspend</code> | function called from core code on suspend once per chip |
| <code>irq_resume</code> | function called from core code on resume once per chip |
| <code>irq_pm_shutdown</code> | function called from core code on shutdown once per chip |
| <code>irq_calc_mask</code> | Optional function to set <code>irq_data.mask</code> for special cases |
| <code>irq_print_chip</code> | optional to print special chip info in <code>show_interrupts</code> |
| <code>irq_request_resources</code> | optional to request resources before calling any other callback related to this irq |
| <code>irq_release_resources</code> | optional to release resources acquired with <code>irq_request_resources</code> |
| <code>flags</code> | chip specific flags |

Name

struct irq_chip_regs — register offsets for struct irq_gci

Synopsis

```
struct irq_chip_regs {  
    unsigned long enable;  
    unsigned long disable;  
    unsigned long mask;  
    unsigned long ack;  
    unsigned long eoi;  
    unsigned long type;  
    unsigned long polarity;  
};
```

Members

| | |
|----------|--|
| enable | Enable register offset to reg_base |
| disable | Disable register offset to reg_base |
| mask | Mask register offset to reg_base |
| ack | Ack register offset to reg_base |
| eoi | Eoi register offset to reg_base |
| type | Type configuration register offset to reg_base |
| polarity | Polarity configuration register offset to reg_base |

Name

struct irq_chip_type — Generic interrupt chip instance for a flow type

Synopsis

```
struct irq_chip_type {  
    struct irq_chip chip;  
    struct irq_chip_regs regs;  
    irq_flow_handler_t handler;  
    u32 type;  
    u32 mask_cache_priv;  
    u32 * mask_cache;  
};
```

Members

| | |
|-----------------|--|
| chip | The real interrupt chip which provides the callbacks |
| regs | Register offsets for this chip |
| handler | Flow handler associated with this chip |
| type | Chip can handle these flow types |
| mask_cache_priv | Cached mask register private to the chip type |
| mask_cache | Pointer to cached mask register |

Description

A `irq_generic_chip` can have several instances of `irq_chip_type` when it requires different functions and register offsets for different flow types.

Name

struct irq_chip_generic — Generic irq chip data structure

Synopsis

```
struct irq_chip_generic {
    raw_spinlock_t lock;
    void __iomem * reg_base;
    unsigned int irq_base;
    unsigned int irq_cnt;
    u32 mask_cache;
    u32 type_cache;
    u32 polarity_cache;
    u32 wake_enabled;
    u32 wake_active;
    unsigned int num_ct;
    void * private;
    unsigned long installed;
    unsigned long unused;
    struct irq_domain * domain;
    struct list_head list;
    struct irq_chip_type chip_types[0];
};
```

Members

| | |
|----------------|---|
| lock | Lock to protect register and cache data access |
| reg_base | Register base address (virtual) |
| irq_base | Interrupt base nr for this chip |
| irq_cnt | Number of interrupts handled by this chip |
| mask_cache | Cached mask register shared between all chip types |
| type_cache | Cached type register |
| polarity_cache | Cached polarity register |
| wake_enabled | Interrupt can wakeup from suspend |
| wake_active | Interrupt is marked as an wakeup from suspend source |
| num_ct | Number of available irq_chip_type instances (usually 1) |
| private | Private data for non generic chip callbacks |
| installed | bitfield to denote installed interrupts |
| unused | bitfield to denote unused interrupts |
| domain | irq domain pointer |

| | |
|----------------------------|--|
| <code>list</code> | List head for keeping track of instances |
| <code>chip_types[0]</code> | Array of interrupt <code>irq_chip_types</code> |

Description

Note, that `irq_chip_generic` can have multiple `irq_chip_type` implementations which can be associated to a particular `irq` line of an `irq_chip_generic` instance. That allows to share and protect state in an `irq_chip_generic` instance when we need to implement different flow mechanisms (level/edge) for it.

Name

enum irq_gc_flags — Initialization flags for generic irq chips

Synopsis

```
enum irq_gc_flags {  
    IRQ_GC_INIT_MASK_CACHE,  
    IRQ_GC_INIT_NESTED_LOCK,  
    IRQ_GC_MASK_CACHE_PER_TYPE,  
    IRQ_GC_NO_MASK  
};
```

Constants

| | |
|----------------------------|--|
| IRQ_GC_INIT_MASK_CACHE | Initialize the mask_cache by reading mask reg |
| IRQ_GC_INIT_NESTED_LOCK | Set the lock class of the irqs to nested for irq chips which need to call irq_set_wake on the parent irq. Usually GPIO implementations |
| IRQ_GC_MASK_CACHE_PER_TYPE | Mask cache is chip type private |
| IRQ_GC_NO_MASK | Do not calculate irq_data->mask |

Name

struct irqaction — per interrupt action descriptor

Synopsis

```
struct irqaction {
    irq_handler_t handler;
    void * dev_id;
    void __percpu * percpu_dev_id;
    struct irqaction * next;
    irq_handler_t thread_fn;
    struct task_struct * thread;
    unsigned int irq;
    unsigned int flags;
    unsigned long thread_flags;
    unsigned long thread_mask;
    const char * name;
    struct proc_dir_entry * dir;
};
```

Members

| | |
|---------------|---|
| handler | interrupt handler function |
| dev_id | cookie to identify the device |
| percpu_dev_id | cookie to identify the device |
| next | pointer to the next irqaction for shared interrupts |
| thread_fn | interrupt handler function for threaded interrupts |
| thread | thread pointer for threaded interrupts |
| irq | interrupt number |
| flags | flags (see IRQF_* above) |
| thread_flags | flags related to <i>thread</i> |
| thread_mask | bitmask for keeping track of <i>thread</i> activity |
| name | name of the device |
| dir | pointer to the proc/irq/NN/name entry |

Name

struct irq_affinity_notify — context for notification of IRQ affinity changes

Synopsis

```
struct irq_affinity_notify {
    unsigned int irq;
    struct kref kref;
    struct work_struct work;
    void (* notify) (struct irq_affinity_notify *, const cpumask_t *mask);
    void (* release) (struct kref *ref);
};
```

Members

| | |
|---------|--|
| irq | Interrupt to which notification applies |
| kref | Reference count, for internal use |
| work | Work item, for internal use |
| notify | Function to be called on change. This will be called in process context. |
| release | Function to be called on release. This will be called in process context. Once registered, the structure must only be freed when this function is called or later. |

Name

`irq_set_affinity` — Set the irq affinity of a given irq

Synopsis

```
int irq_set_affinity (unsigned int irq, const struct cpumask * cpumask);
```

Arguments

irq Interrupt to set affinity

cpumask cpumask

Description

Fails if cpumask does not contain an online CPU

Name

`irq_force_affinity` — Force the irq affinity of a given irq

Synopsis

```
int irq_force_affinity (unsigned int irq, const struct cpumask *  
cpumask);
```

Arguments

irq Interrupt to set affinity

cpumask cpumask

Description

Same as `irq_set_affinity`, but without checking the mask against online cpus.

Solely for low level cpu hotplug code, where we need to make per cpu interrupts affine before the cpu becomes online.

Chapter 9. Public Functions Provided

This chapter contains the autogenerated documentation of the kernel API functions which are exported.

Name

synchronize_hardirq — wait for pending hard IRQ handlers (on other CPUs)

Synopsis

```
void synchronize_hardirq (unsigned int irq);
```

Arguments

irq interrupt number to wait for

Description

This function waits for any pending hard IRQ handlers for this interrupt to complete before returning. If you use this function while holding a resource the IRQ handler may need you will deadlock. It does not take associated threaded handlers into account.

Do not use this for shutdown scenarios where you must be sure that all parts (hardirq and threaded handler) have completed.

This function may be called - with care - from IRQ context.

Name

synchronize_irq — wait for pending IRQ handlers (on other CPUs)

Synopsis

```
void synchronize_irq (unsigned int irq);
```

Arguments

irq interrupt number to wait for

Description

This function waits for any pending IRQ handlers for this interrupt to complete before returning. If you use this function while holding a resource the IRQ handler may need you will deadlock.

This function may be called - with care - from IRQ context.

Name

`irq_set_affinity_notifier` — control notification of IRQ affinity changes

Synopsis

```
int    irq_set_affinity_notifier    (unsigned    int    irq,    struct
irq_affinity_notify * notify);
```

Arguments

irq Interrupt for which to enable/disable notification

notify Context for notification, or NULL to disable notification. Function pointers must be initialised; the other fields will be initialised by this function.

Description

Must be called in process context. Notification may only be enabled after the IRQ is allocated and must be disabled before the IRQ is freed using `free_irq`.

Name

`disable_irq_nosync` — disable an irq without waiting

Synopsis

```
void disable_irq_nosync (unsigned int irq);
```

Arguments

irq Interrupt to disable

Description

Disable the selected interrupt line. Disables and Enables are nested. Unlike `disable_irq`, this function does not ensure existing instances of the IRQ handler have completed before returning.

This function may be called from IRQ context.

Name

`disable_irq` — disable an irq and wait for completion

Synopsis

```
void disable_irq (unsigned int irq);
```

Arguments

irq Interrupt to disable

Description

Disable the selected interrupt line. Enables and Disables are nested. This function waits for any pending IRQ handlers for this interrupt to complete before returning. If you use this function while holding a resource the IRQ handler may need you will deadlock.

This function may be called - with care - from IRQ context.

Name

`enable_irq` — enable handling of an irq

Synopsis

```
void enable_irq (unsigned int irq);
```

Arguments

irq Interrupt to enable

Description

Undoes the effect of one call to `disable_irq`. If this matches the last disable, processing of interrupts on this IRQ line is re-enabled.

This function may be called from IRQ context only when `desc->irq_data.chip->bus_lock` and `desc->chip->bus_sync_unlock` are NULL !

Name

`irq_set_irq_wake` — control irq power management wakeup

Synopsis

```
int irq_set_irq_wake (unsigned int irq, unsigned int on);
```

Arguments

irq interrupt to control

on enable/disable power management wakeup

Description

Enable/disable power management wakeup mode, which is disabled by default. Enables and disables must match, just as they match for non-wakeup mode support.

Wakeup mode lets this IRQ wake the system from sleep states like “suspend to RAM”.

Name

`irq_wake_thread` — wake the irq thread for the action identified by `dev_id`

Synopsis

```
void irq_wake_thread (unsigned int irq, void * dev_id);
```

Arguments

irq Interrupt line

dev_id Device identity for which the thread should be woken

Name

`setup_irq` — setup an interrupt

Synopsis

```
int setup_irq (unsigned int irq, struct irqaction * act);
```

Arguments

irq Interrupt line to setup

act irqaction for the interrupt

Description

Used to statically setup interrupts in the early boot process.

Name

`remove_irq` — free an interrupt

Synopsis

```
void remove_irq (unsigned int irq, struct irqaction * act);
```

Arguments

irq Interrupt line to free

act irqaction for the interrupt

Description

Used to remove interrupts statically setup by the early boot process.

Name

`free_irq` — free an interrupt allocated with `request_irq`

Synopsis

```
void free_irq (unsigned int irq, void * dev_id);
```

Arguments

irq Interrupt line to free

dev_id Device identity to free

Description

Remove an interrupt handler. The handler is removed and if the interrupt line is no longer in use by any driver it is disabled. On a shared IRQ the caller must ensure the interrupt is disabled on the card it drives before calling this function. The function does not return until any executing interrupts for this IRQ have completed.

This function must not be called from interrupt context.

Name

`request_threaded_irq` — allocate an interrupt line

Synopsis

```
int request_threaded_irq (unsigned int irq, irq_handler_t handler,  
irq_handler_t thread_fn, unsigned long irqflags, const char * devname,  
void * dev_id);
```

Arguments

| | |
|------------------|--|
| <i>irq</i> | Interrupt line to allocate |
| <i>handler</i> | Function to be called when the IRQ occurs. Primary handler for threaded interrupts If NULL and <i>thread_fn</i> != NULL the default primary handler is installed |
| <i>thread_fn</i> | Function called from the irq handler thread If NULL, no irq thread is created |
| <i>irqflags</i> | Interrupt type flags |
| <i>devname</i> | An ascii name for the claiming device |
| <i>dev_id</i> | A cookie passed back to the handler function |

Description

This call allocates interrupt resources and enables the interrupt line and IRQ handling. From the point this call is made your handler function may be invoked. Since your handler function must clear any interrupt the board raises, you must take care both to initialise your hardware and to set up the interrupt handler in the right order.

If you want to set up a threaded irq handler for your device then you need to supply *handler* and *thread_fn*. *handler* is still called in hard interrupt context and has to check whether the interrupt originates from the device. If yes it needs to disable the interrupt on the device and return `IRQ_WAKE_THREAD` which will wake up the handler thread and run *thread_fn*. This split handler design is necessary to support shared interrupts.

Dev_id must be globally unique. Normally the address of the device data structure is used as the cookie. Since the handler receives this value it makes sense to use it.

If your interrupt is shared you must pass a non NULL *dev_id* as this is required when freeing the interrupt.

Flags

`IRQF_SHARED` Interrupt is shared `IRQF_TRIGGER_*` Specify active edge(s) or level

Name

`request_any_context_irq` — allocate an interrupt line

Synopsis

```
int request_any_context_irq (unsigned int irq, irq_handler_t handler,
unsigned long flags, const char * name, void * dev_id);
```

Arguments

| | |
|----------------|--|
| <i>irq</i> | Interrupt line to allocate |
| <i>handler</i> | Function to be called when the IRQ occurs. Threaded handler for threaded interrupts. |
| <i>flags</i> | Interrupt type flags |
| <i>name</i> | An ascii name for the claiming device |
| <i>dev_id</i> | A cookie passed back to the handler function |

Description

This call allocates interrupt resources and enables the interrupt line and IRQ handling. It selects either a hardirq or threaded handling method depending on the context.

On failure, it returns a negative value. On success, it returns either `IRQC_IS_HARDIRQ` or `IRQC_IS_NESTED`.

Name

`irq_set_chip` — set the irq chip for an irq

Synopsis

```
int irq_set_chip (unsigned int irq, struct irq_chip * chip);
```

Arguments

irq irq number

chip pointer to irq chip description structure

Name

`irq_set_irq_type` — set the irq trigger type for an irq

Synopsis

```
int irq_set_irq_type (unsigned int irq, unsigned int type);
```

Arguments

irq irq number

type IRQ_TYPE_{LEVEL,EDGE}_* value - see include/linux/irq.h

Name

`irq_set_handler_data` — set irq handler data for an irq

Synopsis

```
int irq_set_handler_data (unsigned int irq, void * data);
```

Arguments

irq Interrupt number

data Pointer to interrupt specific data

Description

Set the hardware irq controller data for an irq

Name

`irq_set_chip_data` — set irq chip data for an irq

Synopsis

```
int irq_set_chip_data (unsigned int irq, void * data);
```

Arguments

irq Interrupt number

data Pointer to chip specific data

Description

Set the hardware irq chip data for an irq

Name

`handle_simple_irq` — Simple and software-decoded IRQs.

Synopsis

```
void handle_simple_irq (unsigned int irq, struct irq_desc * desc);
```

Arguments

irq the interrupt number

desc the interrupt description structure for this irq

Description

Simple interrupts are either sent from a demultiplexing interrupt handler or come from hardware, where no interrupt hardware control is necessary.

Note

The caller is expected to handle the ack, clear, mask and unmask issues if necessary.

Name

`handle_level_irq` — Level type irq handler

Synopsis

```
void handle_level_irq (unsigned int irq, struct irq_desc * desc);
```

Arguments

irq the interrupt number

desc the interrupt description structure for this irq

Description

Level type interrupts are active as long as the hardware line has the active level. This may require to mask the interrupt and unmask it after the associated handler has acknowledged the device, so the interrupt line is back to inactive.

Name

`handle_fasteoi_irq` — irq handler for transparent controllers

Synopsis

```
void handle_fasteoi_irq (unsigned int irq, struct irq_desc * desc);
```

Arguments

irq the interrupt number

desc the interrupt description structure for this irq

Only a single callback will be issued to the chip

an `->eoi` call when the interrupt has been serviced. This enables support for modern forms of interrupt handlers, which handle the flow details in hardware, transparently.

Name

`handle_edge_irq` — edge type IRQ handler

Synopsis

```
void handle_edge_irq (unsigned int irq, struct irq_desc * desc);
```

Arguments

irq the interrupt number

desc the interrupt description structure for this irq

Description

Interrupt occurs on the falling and/or rising edge of a hardware signal. The occurrence is latched into the irq controller hardware and must be acked in order to be reenabled. After the ack another interrupt can happen on the same source even before the first one is handled by the associated event handler. If this happens it might be necessary to disable (mask) the interrupt depending on the controller hardware. This requires to reenale the interrupt inside of the loop which handles the interrupts which have arrived while the handler was running. If all pending interrupts are handled, the loop is left.

Chapter 10. Internal Functions Provided

This chapter contains the autogenerated documentation of the internal functions.

Name

`irq_get_next_irq` — get next allocated irq number

Synopsis

```
unsigned int irq_get_next_irq (unsigned int offset);
```

Arguments

offset where to start the search

Description

Returns next irq number after offset or `nr_irqs` if none is found.

Name

`handle_bad_irq` — handle spurious and unhandled irqs

Synopsis

```
void handle_bad_irq (unsigned int irq, struct irq_desc * desc);
```

Arguments

irq the interrupt number

desc description of the interrupt

Description

Handles spurious and unhandled IRQ's. It also prints a debugmessage.

Name

`irq_set_msi_desc_off` — set MSI descriptor data for an irq at offset

Synopsis

```
int irq_set_msi_desc_off (unsigned int irq_base, unsigned int  
irq_offset, struct msi_desc * entry);
```

Arguments

| | |
|-------------------|--------------------------------|
| <i>irq_base</i> | Interrupt number base |
| <i>irq_offset</i> | Interrupt number offset |
| <i>entry</i> | Pointer to MSI descriptor data |

Description

Set the MSI descriptor entry for an irq at offset

Name

`irq_set_msi_desc` — set MSI descriptor data for an irq

Synopsis

```
int irq_set_msi_desc (unsigned int irq, struct msi_desc * entry);
```

Arguments

irq Interrupt number

entry Pointer to MSI descriptor data

Description

Set the MSI descriptor entry for an irq

Name

`irq_disable` — Mark interrupt disabled

Synopsis

```
void irq_disable (struct irq_desc * desc);
```

Arguments

desc irq descriptor which should be disabled

Description

If the chip does not implement the `irq_disable` callback, we use a lazy disable approach. That means we mark the interrupt disabled, but leave the hardware unmasked. That's an optimization because we avoid the hardware access for the common case where no interrupt happens after we marked it disabled. If an interrupt happens, then the interrupt flow handler masks the line at the hardware level and marks it pending.

Name

`handle_edge_eoi_irq` — edge eoi type IRQ handler

Synopsis

```
void handle_edge_eoi_irq (unsigned int irq, struct irq_desc * desc);
```

Arguments

irq the interrupt number

desc the interrupt description structure for this irq

Description

Similar as the above `handle_edge_irq`, but using eoi and w/o the mask/unmask logic.

Name

`handle_percpu_irq` — Per CPU local irq handler

Synopsis

```
void handle_percpu_irq (unsigned int irq, struct irq_desc * desc);
```

Arguments

irq the interrupt number

desc the interrupt description structure for this irq

Description

Per CPU interrupts on SMP machines without locking requirements

Name

`handle_percpu_devid_irq` — Per CPU local irq handler with per cpu dev ids

Synopsis

```
void handle_percpu_devid_irq (unsigned int irq, struct irq_desc * desc);
```

Arguments

irq the interrupt number

desc the interrupt description structure for this irq

Description

Per CPU interrupts on SMP machines without locking requirements. Same as `handle_percpu_irq` above but with the following extras:

action->percpu_dev_id is a pointer to percpu variables which contain the real device id for the cpu on which this handler is called

Name

`irq_cpu_online` — Invoke all `irq_cpu_online` functions.

Synopsis

```
void irq_cpu_online ( void );
```

Arguments

void no arguments

Description

Iterate through all `irqs` and invoke the `chip.irq_cpu_online` for each.

Name

`irq_cpu_offline` — Invoke all `irq_cpu_offline` functions.

Synopsis

```
void irq_cpu_offline ( void );
```

Arguments

void no arguments

Description

Iterate through all `irqs` and invoke the `chip.irq_cpu_offline` for each.

Chapter 11. Credits

The following people have contributed to this document:

1. Thomas Gleixner<tglx@linutronix.de>
2. Ingo Molnar<mingo@elte.hu>