

The μ racoli Source Package

REVISION HISTORY			
NUMBER	DATE	DESCRIPTION	NAME

Contents

1	Overview	1
2	Compiling the Libraries	1
3	Wireless UART	2
4	Multiport Serial Terminal Program	2
5	Sniffer Firmware	3
6	Wireless Bootloader	3
7	Examples	3

1 Overview

This package contains the uracoli-source code.

src	Source code of radio and ioutil library.
inc	The library header file.
wuart	The wireless UART application.
sniffer	The source code of the sniffer firmware.
wibo	The wireless bootloader source code, host application and examples.
xmpl	Some example applications, that illustrate how to use the μ racoli functions.

In order to build the libraries and applications you need an installed AVR toolchain.

avr-gcc	AVR GCC C-compiler which we need to compile the libraries and the test examples
avr-binutils	Linker, Object File Converter, ..
avr-libc	Standard C library which provides a good set of C standard functions
avrdude	Tool to transfer the machine code (.hex files) via ISP or JTAG AVR interface to the internal Flash memory and/or EEPROM.
avr-gdb	GNU debugger to debug AVR programs
AVaRICE	This tool interfaces the AVR GNU debugger with the AVR JTAG interface which allows real in-circuit debugging

A detailed installation description is available at <http://uracoli.nongnu.org/avrtools.html>.

2 Compiling the Libraries

The libraries can be build with make. In order to get an overview, if your board is supported, type

```
make -C src/ list
```

The libraries for e.g. the "radiofaro" board, are build with the command:

```
make -C src radiofaro
```

This will create the directory lib and the uracoli-library for radiofaro.

```
$ls lib/  
liburacoli_radiofaro.a
```


5 Sniffer Firmware

With the sniffer firmware the frames exchanged in an IEEE 802.15.4 network can be captured and transmitted over the serial interface to the PC. This firmware is intended for use with a the Python script `sniffer.py` and [wireshark](#). The script together with the documentation, which explains the sniffer setup, can be found in the package `uracoli-sniffer-<version>.zip` on <http://uracoli.nongnu.org/download.html>.

The sniffer firmware can be compiled with the commands

```
make -C src mysnifferboard
make -C sniffer mysnifferboard
```

For which boards the sniffer application is available, you can find out with the command:

```
make -C sniffer list
```

6 Wireless Bootloader

The wireless bootloader (WiBo) is an application that resides in the bootloader section of the AVR and therefore it can erase and rewrite the programm flash memory. In Difference to a regular bootloader, WiBo receives its data over the RF link. WiBo modifies the flash directly, therefore no special backup flash memory, like in other over the air upgrade (OTA) solutions, is required on the transceiver board.

A detailed description how WiBo is used can be found in `doc/uracoli-wibo.pdf` or `doc/uracoli-wibo.txt`.

7 Examples

The example source code can be found in the directory `xmpl/`. This simple example programmes are thought as starters for your application.

<code>xmpl_leds.c</code>	Example use of the LED macros
<code>xmpl_key_events.c</code>	Example for key event processing with a single key
<code>xmpl_keys.c</code>	Example use of the KEY macros
<code>xmpl_hif.c</code>	Example for use of the HIF functions
<code>xmpl_hif_echo.c</code>	Example that implements HIF echo, usefull to test the HIF troughput
<code>xmpl_timer.c</code>	Example for using the timer macros
<code>xmpl_dbg.c</code>	Example for use of the DBG_XXX macros
<code>xmpl_linbuf_tx.c</code>	Example use of the buffer functions
<code>xmpl_trx_base.c</code>	Example for accessing the transceiver
<code>xmpl_trx_echo.c</code>	Example for echoing received frames
<code>xmpl_trx_rxaack.c</code>	Example for receiving frames in rx_aack mode
<code>xmpl_trx_rx.c</code>	Example for receiving frames

xmpl_trx_txaret.c Example for transmitting frames in tx_aret mode

xmpl_trx_tx.c Example for transmitting frames

xmpl_radio_range.c Example use of the radio and ioutil functions for a simple range test

xmpl_radio_stream.c Example use of the radio stream functions

The example firmware can be build with the following commands:

```
make -C src myboard
make -C xmpl -f xmpl_<myexample>.mk myboard
```

Note: Some of the examples are not available on all boards, due to the lack of some hardware features, e.g. if the LEDs, the KEYS or/and the HIF is absent. A list of supported boards of the example can be obtained by:

```
make -C xmpl -f xmpl_<myexample>.mk list
```